

KF2500A

2.5 TON DIRECT AIR HOT STAMPING PRESS

FEATURES

- Dual Hardened Steel Guide Rods in Ball Bushings
- Precision Microm Depth Stop
- Dovetailed Die Holder
- Tool Free Height Adjustment
- Accurate Easy-to-Adjust Foil Advance
- Simple to Unload Foil Takeup
- Ground Steel Worktable
- Head Speed Controls
- Heavy Duty Extra Rigid Frame
- Air Filter, Pressure Regulator & Automatic Lubricator

2.5 TON
CAPACITY



KF
KENSOL-FRANKLIN

HOT STAMPING MACHINES

KF2500A

DIRECT AIR HOT STAMPING PRESS

SPECIFICATIONS

Max Opening Under Head:	16"
Hot Stamps Items up to:	13" (Optional additional shut height available)
Overall Height:	47"
Net Weight:	600 lbs.
Head Stroke:	0-3" Standard
Throat Depth:	7.5"
Pressure Range:	0 - 2.5 Tons
Foil Advance:	Electric Motor
Heat Control:	Solid State Digital Indicating
Standard Head Sizes:	6" x 8" - 1050 Watts 6" x 12" - 2000 Watts 10" x 15" - 4000 Watts
Press Controls:	Programmable Logic-Based System with Operator Interface Panel
Actuation:	Simultaneous Lite-Touch Anti-Tie Down 2 Hand Buttons w/Pinch Point Interlock
Electrical Requirements:	6" x 8" 110V A.C. Larger sizes 220V, 1 Phase
Compressed Air Requirements:	1.10 Cu. Ft. Free Air/Stroke @ 80 p.s.i.
Work Table:	Pre-Drilled Ground Steel

STANDARD VARIATIONS AVAILABLE

- Specialty Code Conformance: NEMA, JIC, etc.
- Additional Vertical Height Capability
- Additional Throat Depth
- Longer Head Stroke
- Larger Work Table
- Larger Platen Sizes
- Expanded Dwell Timer Range
- Heat Transfer Indexer

AUTOMATION AVAILABLE

- Auto Cycle Slide Table
- Rotary Index Table
- Automatic Parts Loading Systems
- Automatic Parts Removal Systems
- Special Protective Enclosures
- "Light Curtain" Operator Protection



HOT STAMPING MACHINES

Phone: 508-528-2000 Fax: 508-520-7129

Mfg. By Nationwide Parts & Services

1 Main St. Bldg. 16 Suite 5 Whitinsville, MA. 01588

Made in U.S.A.

Appropriate safety devices should always be used. KF Kensol-Franklin will quote or advise on protective equipment for your application upon request.

